LS1500 (ACCESSORY)

- Accessory modules designed for LS1500 chassis with 1U/2U units high
- Breaker extension unit
- Blind plug-in units for proper air venting

Power supply system of LS1500 type, in addition to power supply management unit and rectifier units, contains several accessory units for output extensions or for blinding free rectifiers positions to ensure a proper air venting.

LS300.Z FB01 module is a plug-in module for output distribution with 4 breakers up to 10A with switch equipped with LED signalization LS1500 1U blind plug-in unit is intended for proper air venting of LS1500 chassis with 1U high (44mm) LS1500 2U blind plug-in unit is intended for proper air venting of LS1500 chassis with 2U high (88mm)

| MODEL SPECIFICATIONS | LS300.Z FB01 1U | LS1500 blinder 1U | LS1500 2U blinder 2U |
|--------------------------|---|---|---|
| PICTURE | | 19 (C) | 9 0 |
| Description | Output distribution unit with 4 switched on/off breaker outputs up to 10A | 1U blinder for proper air venting of LS1500 chassis | 2U blinder for proper air venting of LS1500 chassis |
| Signalization | LED signalization of switched off output | | |
| Output | 4x output up to 10A/80V | | |
| Mounting type | Plug-in unit | Plug-in unit | Plug-in unit |
| Dimension W x H x D (mm) | 89 x 45(1U) x 250 | 89 x 45(1U) x 36mm | 89 x 88(2U) x 36mm |
| Weight (kg) | 0.33kg | 0.05kg | 0.085kg |
| Degree of protection | IP20 | IP20 | IP20 |
| Part No. | IP.9431.043.01 | IP.0000.000.02 | IP.0000.000.03 |