







-  **Accessory modules designed for LS1500 chassis with 1U/2U units high**
-  **Breaker extension unit**
-  **Blind plug-in units for proper air venting**

Power supply system of LS1500 type, in addition to power supply management unit and rectifier units, contains several accessory units for output extensions or for blinding free rectifiers positions to ensure a proper air venting.

LS300.Z FB01 module is a plug-in module for output distribution with 4 breakers up to 10A with switch equipped with LED signalization

LS1500 1U blind plug-in unit is intended for proper air venting of LS1500 chassis with 1U high (44mm)

LS1500 2U blind plug-in unit is intended for proper air venting of LS1500 chassis with 2U high (88mm)

MODEL SPECIFICATIONS	LS300.Z FB01 1U	LS1500 1U blind plug-in	LS1500 2U blind plug-in
PICTURE			
Description	Output distribution unit with 4 switched on/off breaker outputs up to 10A	1U plug-in unit for proper air venting of LS1500 chassis	2U plug-in unit for proper air venting of LS1500 chassis
Local signaling	LED signalization of switched off output		
Output	4x output up to 10A/80V		
Mounting type	Plug-in module	Plug-in module	Plug-in module
Dimension W x H x D (mm)	89 x 45(1U) x 250	89 x 45(1U) x 36mm	89 x 88(2U) x 36mm
Weight (kg)	0.33kg	0.05kg	0.085kg
Degree of protection	IP20	IP20	IP20
Part No.	IP.9431.043.01	IP.0000.000.02	IP.0000.000.03